

The KAIVAC 1250

EQUIPMENT SPECIFICATIONS

DESCRIPTION

Water Tank	45 Litres (12 Gallons)
Spray Time	12 Minutes
Restroom Fixtures/Tank	~45
Flow Rate	3.8 L/min
Pressure	34.5 bars (500 psi)
Vac Tank	30 Litres
See-Through Vac Tank	Yes
Dump Hose	66 cm Long
Toilet Dumping	Yes
Vac Tank Cleanout	100%
Method of Dumping	Dump Hose
Vac Motor Lift	330 cm
Vac CFM	3172 L/min (112cfm)
HEPA Blow Feature	483 km/h
HEPA Filtered Exhaust	Yes – Replaceable
Decibels (dB)	69 dB

CHEMICAL

Moulded-In Chemical Holder	1 Gallon, 2 Quart
Chemical Switching	Single/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

ELECTRICAL

Volts (Universal)	100-240V; 50-60 Hz
Amps Total	14.5 amp
RCD	Yes

CORDS AND HOSES

Vac Hose	15 m Slinky
Spray Line	14 m
Quick-Connect Gun	Yes
Electrical Cord	7.5 m
Blow Hose	10 m Slinky

BODY

Rotational Mould	Yes
Removable Engine Compartment	Yes – Black Box Technology
Weight	42.4 kg
Size (H x L x W)	97 x 56 x 51 cm
Hard Rubber Tyre	2 x 12.7 cm
Casters	2 x 10.2 cm Locking
Handle	Moulded-In
Parking Brake	Yes

TOOLS INCLUDED

Vac Wand Aluminium	Yes
Squeegee Head with Brushes	35 cm
Blow Nozzle	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
Tote Bag	57 Litres

OPTIONAL TOOLS & ATTACHMENTS

KaiTutor Onboard Training System	Compatible
Gatling Tool Range	Compatible
Carpet Extraction Tool	Compatible
Upholstery Tool	Compatible
Grout Turbo Tool	Compatible
Trash Compactor	Compatible
Wide Area Squeegee Head	Compatible
Stair Climbing Wheels	Compatible

WARRANTY

With Kaivac Chemical Usage	24 Months
With Other Chemicals	12 Months

