

Quick-Change
Power Pack
Available



KaiVac® 1250

Specifications

Warranty

| | |
|----------------------------|-----------|
| With KaiVac Chemical Usage | 24 Months |
| With Other Chemicals | 12 Months |

Electrical Specifications

| | |
|-------------------|--------------------|
| Volts (US) | 110 Volt – 60 Hz |
| Volts (Universal) | 100-240Hz; 50-60Hz |
| Amps Total | 7 amp |
| Electric Cord | 8 m |
| RCD | Yes |

Tools and Attachment Specifications

| | |
|---------------------------|------------------------|
| Aluminum Vacuum Wand | Yes |
| Blow Hose & Nozzle | Yes |
| Window Squeegee | Yes |
| Gulper Tool | Yes |
| 36cm Squeegee Head Brush | Yes |
| 36cm Squeegee Head | Yes |
| Spray Line with Spray Gun | Yes – 14 m |
| Training Materials | Yes |
| Tote Bag | Yes |
| Vacuum Hose | 14 m Slinky |
| Cleaning Width | 36 cm with Vacuum Wand |

Physical Specifications

*dimensions and capacities are approximate

| | |
|---------------------------------------|----------------------------|
| Weight | 43 kg |
| (H x L X W) Shipping Size | 125 cm x 66 cm x 61 cm |
| (H x L X W) As Assembled | 97 cm x 56 cm x 51 cm |
| Solution Tank | 43 l |
| Vacuum Tank | 35 l |
| Variable Flow Spigot | No |
| Method of Dumping | Dump Hose |
| Dump Hose | 66 cm long |
| Toilet Dumping | Yes |
| Vacuum Motor Lift | 330 cm |
| Vacuum CFM | 3172 l/min |
| Decibels (dB) | 69 dB |
| Pump System | 500 PSI |
| Hard Rubber Tires | 13 cm |
| Flat-free Non-marking Pneumatic Tires | N/A |
| Caster | 10 cm |
| Blow Hose | 10 m |
| Removable Engine Compartment | Yes – Black Box Technology |
| HEPA Blow Feature | 483 kmh |
| HEPA Filtered Exhaust | Yes – Replaceable |

